

LOW BED

45 Tn



LeciTrailer



DIMENSIONS

- **Length:** 12.050 mm.
- **Width:** 2.550 mm. can be widened to 3.000 mm. with side rave integrated wideners.
- **5th wheel height:** 1.150 mm. to 1.250 mm (check for other heights).
- **King-pin distance:** 1.000 mm.
- **Weight:** 8.440 kgs.

	MMA	MMTA
King-pin	12.000	15.000
1st axle	8.000	10.300
2nd axle	8.000	10.300
3rd axle	8.000	10.300
Total	35.000	45.900 (*)

STRUCTURE

- Main beams in double T section in high elasticity limit steel.
- Neck 280 mm as per ISO 1726 regulation.
- IPEA-120 Crossmembers at 400mm distance.
- Lowered structure to easy upper part access.
- Cold laminated side rave, in HB400, with side rave integrated rims.
- Reinforced mechanical 2 speed landing legs.
- Reinforced rear landing legs.
- Lateral movable rear ramps.
- 40 mm plain wood floor.

TRIDEM

- 3 brake drum axles.
- Pneumatical suspension actuated by 5 ways valve.
- 13 tyres, 245/70 R 17,5 dimension.

- ABS 1 axle.
- CE Homologated 2 circuits brake instalation.
- Pneumatical chamber parking brake.

ELECTRICAL AND PNEUMATICAL INSTALACION

- Pneumatical ISO coupling head with filter incorporated.
- Armoured electrical instalation as per ADR regulation 24V.
- 3 ISO connectors: 2 of 7 poles (24N and 24S) and 1 of 15 poles.
- 7 services optical group with registration plate support.
- Reverse gear warning sound device.
- LED yellow side lights.

FINISHINGS

- Shot blasted metallic structure (SA 2^{1/2}).
- Prime finishing-Epoxy (2 components).
- Acrylic Polyurethane coating (2 components).
- RAL colour to be chosen.

EQUIPMENT

- Mudguard system as per actual regulation.
- 400mm height steel front and side walls in upper part of vehicle.
- Spare wheel in front part.
- Cyclist side protection.
- Long vehicle plates.
- Wheel keys.
- Autonomous electrohydraulic equipment for lifting rear ramps.

(*) Reinforced neck MMTA 50.900 Kg.-- MMTA King-pin 20.000 Kg. Double king-pin location for 3 axles trucks.

OPTIONAL EQUIPMENT

- Mechanical suspension.
- Self steering axle.
- First axle lifter (only available in pneumatical suspension).
- Hubodometer.
- EBS+RSS with 1 or 2 sensorized axles.
- Pressure load control.
- Chequered plate floor 4/6 mm.
- PVC tool box (fixed in chassis neck).
- 6 kgs. Fire extinguisher and its box.
- 30 liters PVC water deposit.
- Exceptional transport kit.
- Removable neck acces ramps, in anti skidding aluminium.
- Hydraulic equipment for ramps lifting (only for prepared tractor heads).
- Tramex floor rear ramps, in galvanized steel.
- Double Ramps extra-length.
- Dissambled side walls in gooseneck.
- Electrical winch 5Tn.
- Hydraulic winch 10 Tn.
- King-pin de 3^{1/2}".

